

R304326 Connection Module Cat.5e, 1xRJ45/u, 100x

090.5327

Scope of supply

- RJ45 Cat.5e connection module, unshielded
- Mounting plate
- Dust cover
- Cable tie
- Installation instructions

Weight

8.643 G

Technical Data

Standardisation	IEC 60603-7: Electrical Characteristics of the Telecommunication Outlets ISO/IEC 11801 ed. 2.2: June 2011; EN 50173-1: May 2011;	
Connector class	Connection module	
Connector type (A)	RJ45	
Category connector (A)	Cat.5e	
Shielding - connector (A)	No	
Holder for connector / module	Support Plate	
Color	light gray	
Dimensions	16.4 x 21.4 x 40.9 mm	
Material	plastic: PC, UL 94 V-0	
Wiring diagram	TIA 568-A / TIA 568-B	
Poles	8	

Connection Module, Cat.5e, 100 x RJ45, unshielded

RJ45 connection module of Category 5, for the setting up of transmission channels of class D with up to 4 plugged connections, complies with Category 5 requirements of the standards ISO/IEC 11801 ed. 2.2, June 2011, EN 50173-1, May 2011 (DIN EN 50173-1) as well as TIA 568-C, de-embedded tested in acc. with IEC 60603-7-2, interoperable and backwards compatible with Category 5e (2000) and Category 5 (1995).

Suitable for 1GBASE-T applications in acc. with IEEE 802.3™ Section Three over 100 m.

Tested in line with R&M's manufacturing control.

Compatible with RJ standard plugs (RJ11, RJ12, RJ45), PCB-free and tool-free Easy-Lock connection of installation cables AWG 24-22 (0.5 mm-0.65 mm) and flexible cables AWG 26/7-AWG 22/7 (as of production date 07461). Parallel pair termination without crossover in acc. with TIA 568-A/B, gold-plated bronze contacts for >1000 mating cycles, IDC contacts with single-wire strain relief and >20 insertion cycles, contact resistance 1000 Veff. PoE and PoE + compatible according to IEC 60512-99-001. With integral cable strain relief, including dust cover.

Material: halogen-free and heavy-metal free in acc. with EU directives RoHS 2.

Special installer package with connection module Cat.5e, with dust cover, mounting instructions.	plate, cable tie and installatior
Reichle & De-Massari AG. Subject to technical modifications. 2 / 2 www.rdm.com	15.07.2015
,	-