

R810205 FO Field LC, Grade Bmf, PC, beige, OM4 fiber stub, 250µm fibers up to 0.9mm fibers (2014)

090.6847

**Description**

Field-terminable LC/PC connector, Grade Bmf/3, individual packaged incl. stripping chart and QR code with installation instructions.
Color beige, strain relief pigtail white.

Weight

3.800 G

Availability

- Available until 04.2016
- Replaced by part Number R820791

Technical Data

Standardisation	according to IEC 61754-20
Connector class	connector
Connector type (A)	LC
Polishing connector (A)	PC
Attenuation grade IL - connector (A)	Bm
Connector color (A)	beige

Tender text

FO Field LC, Grade Bmf, PC, beige, OM4 fiber stub, 250µm fibers up to 0.9mm fibers
Field-terminable connector, LC PC, Grade Bmf/3, in compliance with IEC 61754-20 (LC) and FprEN 50377-17-1 (draft of standard for field-terminable connectors).
Connector housing made of PBT / UL 94 V-0, beige, (multimode PC), extended unlocking lever for optimum unlocking, fiber stub with 8° cleaved fiber, red semi-transparent push button for fiber fixation and function testing.

Modules & Accessories

R810206	FO Field Patch Set, 1.4-3.0mm cables
R810212	Tool Kit FO Field
R504313	Red Light Source, 2.5+1.25 mm ferrules
R319901	Ferrule Mate, 1.25 mm, for LC
R319904	Cletop Cleaning Spare Cassette
R319903	Cleaning Kit Case FO